

LinHES - Bug # 628: Reduce 'unclutter' agressiveness

Status:	Closed	Priority:	Normal
Author:	bigb	Category:	
Created:	02/22/2010	Assignee:	
Updated:	03/21/2010	Due date:	
Description:	<p>/usr/LH/bin/LinHES-run</p> <p>Has a line that configures clutter, it is currently set to:</p> <pre>/usr/X11R6/bin/unclutter -root -idle 1 -jitter 200 -noevents &</pre> <p>I am suggesting changing this to:</p> <pre>/usr/X11R6/bin/unclutter -root -idle 5 -jitter 5 -noevents &</pre> <p>This is so that the mouse can be controlled in mythbrowser.</p> <p>Not sure if this line is required at all, there is a setting in the frontend to hide the mouse. Mythbrowser is aware of this setting and unhides the mouse when it is running.</p>		

History

03/20/2010 06:44 pm - GregFrost

I have pushed an update to core-testing that has your suggested changes. I found your settings much more useable when browsing/using xterms.

I guess the question is still open as to whether unclutter is needed at all. It may be for things like xine/mplayer? which may not remove the cursor like mythfrontend does.

If there is a valud reason to keep unclutter, then this task can be closed.

03/21/2010 07:26 am - jams

- Target version set to 6.03.00

- Status changed from New to Closed